



## UR5 Technical specifications

Item no. 110105

### 6-axis robot arm with a working radius of 850 mm / 33.5 in

<b>Weight:</b>	18.4 kg / 40.6 lbs		
<b>Payload:</b>	5 kg / 11 lbs		
<b>Reach:</b>	850 mm / 33.5 in		
<b>Joint ranges:</b>	+/- 360°		
<b>Speed:</b>	All joints: 180°/s. Tool: Typical 1 m/s. / 39.4 in/s.		
<b>Repeatability:</b>	+/- 0.1 mm / +/- 0.0039 in (4 mils)		
<b>Footprint:</b>	Ø149 mm / 5.9 in		
<b>Degrees of freedom:</b>	6 rotating joints		
<b>Control box size (WxHxD):</b>	475 mm x 423 mm x 268 mm / 18.7 x 16.7 x 10.6 in		
<b>I/O ports:</b>		Controlbox	Tool conn.
	Digital in	16	2
	Digital out	16	2
	Analog in	2	2
	Analog out	2	-
<b>I/O power supply:</b>	24 V 2A in control box and 12 V/24 V 600 mA in tool		
<b>Communication:</b>	TCP/IP 100 Mbit: IEEE 802.3u, 100BASE-TX Ethernet socket & Modbus TCP		
<b>Programming:</b>	Polyscope graphical user interface on 12 inch touchscreen with mounting		
<b>Noise:</b>	Comparatively noiseless		
<b>IP classification:</b>	IP54		
<b>ISO Class Cleanroom robot arm:</b>	5		
<b>ISO Class Cleanroom control box:</b>	6		
<b>Power consumption:</b>	Approx. 200 watts using a typical program		
<b>Collaboration operation:</b>	15 Advanced Safety Functions Tested in accordance with: EN ISO 13849:2008 PL d EN ISO 10218-1:2011, Clause 5.4.3		
<b>Materials:</b>	Aluminum, PP plastic		
<b>Temperature:</b>	The robot can work in a temperature range of 0-50°C		
<b>Power supply:</b>	100-240 VAC, 50-60 Hz		
<b>Cabling:</b>	Cable between robot and control box (6 m / 236 in) Cable between touchscreen and control box (4.5 m / 177 in)		



email: [info@cobots.ie](mailto:info@cobots.ie)  
tel: +353 (0)21 4633112